



THANK YOU FOR CHOOSING NIKROM!

Installation and Maintenance Guide for optimum performance

Dear customer:

Thank you for your confidence in NIKROM. This dishwasher has been built with special care to offer you the best performance and a long service life.

We congratulate you on your choice: a machine manufactured in Xeresa (Valencia), a small town on the east coast of the Mediterranean that deeply values the sustainability of the planet. That is why we design dishwashers with low energy and water consumption, high productivity in a short time and minimum wastewater discharge.

Even with low pressures (from 1 bar), its rinsing is excellent.

We want to be with you every step of the way. That's why, in addition to thanking you for your purchase, we leave you below:

STEPS FOR CORRECT INSTALLATION

- 1 Check the water quality:**
 - Limescale is one of the main enemies of the equipment. Use the right chemical and recommend the necessary treatment to the customer.
- 2 Check the mains pressure:**
 - The ideal is 2.5 bar.
 - If the pressure is too high, use a flow reducer.
 - If less than 1 bar, you may need booster pump (although NIKROM works perfectly from 1 bar).
- 3 Necessary connections:**
 - Water inlet, drain and electrical connection are a must.
 - The height of the drain in the wall must be below the height of the unit. Otherwise, incorporate automatic drain pump.
- 4 Switching on the unit:**
 - Verify that it reaches the right temperature.
 - The dispensers may be sealed. Check and unblock the membrane if necessary.
- 5 First cycles:**

The equipment will initially load 75% of the tank to accelerate the process. In the first 3-4 cycles the level will be adjusted automatically.
- 6 Customer training:**

Explain basic maintenance to prolong the life of the dishwasher.

DAILY CARE FOR A LONG EQUIPMENT LIFE

- Place the overflow plug before turning on the equipment.
- If there is no automatic soap dispenser, add manually the recommended dose according to the chemical solution.
- (Remember: it only consumes 2L of water per cycle).
- Make sure that the rinse aid bottle is not empty.
- The cleaner the dishes are, the longer the clean water will last and the fewer refills you will need.
- Turn off the appliance before emptying the tank. If the heating element runs dry, it could be damaged
- Remove the overflow plug after use.
- Clean the filters after each day.
- You can wipe the tank with a cloth, but DO NOT use abrasive products.
- If used, be sure to neutralize well to avoid possible rust spots.
- It is recommended to leave the door open overnight for better ventilation.

We are at your disposal for any suggestions, doubts or experiences you would like to share with us.

Share with us at

grupogranita@grupogranita.com

Thank you again for trusting NIKROM.

We hope you enjoy your equipment as much as we have enjoyed making it for you!

We enjoy making it for you!

